

Green Cell

GC Snap

TYPE 2 EV CHARGING CABLE



Ergonomic shape
fit for users' needs



Flexible wire
convenient retraction



Resistant
water and damage
resistant



Hard case
included in the set

SPECIFICATION

Model	EVKABGC01	EVKABGC02	EVKABGC03	EVKABGC04	EVKABGC05	EVKABGC06	EVKABGC07	EVKABGC08
Voltage	1P 200–260 VAC	1P 200–260 VAC	1P 200–260 VAC	1P 200–260 VAC	1P 200–260 VAC	1P 200–260 VAC	1P 200–260 VAC	1P 200–260 VAC
	3P 380–440 VAC	3P 380–440 VAC	3P 380–440 VAC	3P 380–440 VAC				
Current	32 A	32 A	16 A	16 A	32 A	32 A	16 A	16 A
Total Power	22 kW	22 kW	11 kW	11 kW	7.2 kW	7.2 kW	3.6 kW	3.6 kW
Input	Type 2	Type 2	Type 2	Type 2	Type 2	Type 2	Type 2	Type 2
Output	Type 2	Type 2	Type 2	Type 2	Type 2	Type 2	Type 2	Type 2
Cable length	5 m	7 m	5 m	7 m	5 m	7 m	5 m	7 m
Cable variant	5G6.0 + 2x0.5 mm ²	5G6.0 + 2x0.5 mm ²	5G2.5 + 2x0.5 mm ²	5G2.5 + 2x0.5 mm ²	3G6.0 + 2x0.5 mm ²	3G6.0 + 2x0.5 mm ²	3G2.5 + 2x0.5 mm ²	3G2.5 + 2x0.5 mm ²
Cable ø: approx.	17.0 mm	17.0 mm	13.5 mm	13.5 mm	13.5 mm	13.5 mm	11 mm	11 mm
Protection rating	IP54							
Ambient temperature rating	-35 °C to +50 °C							
Weight (+/- 50 g)	3.15 kg	4.45 kg	2 kg	2.4 kg	2.15 kg	2.75 kg	1.5 kg	1.85 kg
Compliance with	EN IEC 61851-1:2019; EN 62196-2:2017; EN 62196-1:2014							

